




Document Name	Specification of UM-1				
Page	1 / 1	Revision	UM1-MESA-155.52000-0001	Date of Issue	2016/02/01

UM-1 SPECIFICATION

	Parameter	Specification
1	Nominal Frequency	155.52000MHz
2	Mode of Vibration	Fundamental
3	Frequency Tolerance	(+25°C±2°C) ±20ppm
4	Operating Temperature Range	-40°C~85°C
5	Stability vs. Temp. Range Ref.	±20ppm
6	Equivalent Series Resistance (ESR)	Less than 15Ω
7	Shunt Capacitance (C0)	Less than 5.0pF
8	Motional Capacitance (C1)	7.0 fF ±20%
9	Load Capacitance (CL)	Series
10	Level of Drive	100μW±10μW
11	Unwanted Response (SPUR)	No Spurious more than -3dB
12	Insulation	More than 500MΩ/DC100V
13	Aging	±2ppm/year
14	Leak Test	1 x 10 ⁻⁸ Pa · m ³ /s [He]
15	Marking	See below
16		

PRODUCT IMAGE	Package	Marking
		



GLOBAL CO., LTD.

Address : 1160 Asari Chuo
 Yamanashi 400-1514 JAPAN
 Tel : +81-55-269-3311 Fax : +81-55-269-2322
 URL : www.global-j.com Mail : info@global-j.com